









**Datenblatt Hublift Flexstep**

Eigenschaft	2+1 Stufen	2+2 Stufen	3 Stufen	3+1 Stufen	4 Stufen	4+1 Stufen	5 Stufen	6 Stufen
Varianten								
Hubhöhe 1 Stop (oberste Stufe = Podest)	240 – 370 mm	240 – 370 mm	360 – 555 mm	360 – 555 mm	480 – 740 mm	480 – 740 mm	600 – 925 mm	720 – 1110 mm
Hubhöhe 2 Stops (oberste Stufe < Podest)	-	-	480 – 740 mm	-	600 – 925 mm	-	720 – 1110 mm	840 – 1250 mm
Plattformlänge	880 mm	1200 mm	910 mm	1190 mm	1215 mm	1495 mm	1520 mm	1825 mm
Außenlänge	1130 mm	1410 mm	1155 mm	1430 mm	1460 mm	1735 mm	1765 mm	2070 mm
Plattformbreite	700, 800, 900, 1000 mm							
Außenbreite	1000, 1100, 1200, 1300 mm							
Eigengewicht	125 – 205 kg							
Tragkraft	400 kg / 2 Pers.							
Stromversorgung	230 V / 50 Hz (1,1 A), max. 90 W, Standby < 6 W							
Geräuschpegel	< 70 dB							
Schutzklasse	IP23							
Arbeitsphase	2 min / 5 min							
Geschwindigkeit	Ca. 40 mm/s							
Haltestelle oben	Optionale vertikale Sicherheitsbarriere, optionale Tür							
Haltestelle unten	Klappbare Auffahrrampe							